The Light Source

20.5 Inch Mega-Truss Pick, I ton



 $I'' \times 6'' \times 2I$ -7/8" 606 IT-6 Aluminum CNC machined with pockets to support one piece of 20.5" truss. Truss is secured by two aluminum pivoting links, half inch swivel bolts, and our solid wing nuts. Has two rigging holes for shackles, motor, or chain hook. The Mega-Truss Pick will suspend one ton of truss, and an additional one ton load suspended under the truss.

The Mega-Truss Pidk has one top and one bottom rigging hole for attaching the truss to a shadkle, motor, or chain hook. The Mega-Truss Pidk will suspend up to one ton of truss load, plus an additional one ton load suspended under the truss. The Mega-Truss Pidk weighs less than 4 pounds for the 12" truss version. Fits 5/8" Shadkle and larger. Other models are available for 12",16", 18", 24", and 30" truss.

Please note that these do not fit a Global Truss or Applied Truss. See Global Truss Picks for correct part # to order. For Applied Truss you will need to call us with specifications.

Use order code with 20.375 when ordering for Total Structures "Element 20.5" truss.

Working Load I ton

Limit

Hardware 1/2"-13 steel swivel eyebolts with our solid aluminum

wing nuts

Dimensions I"×6"×21-7/8" Actual center hole is 1.5" wideActual single

multi-hole is 5/8" wide

Weight 8.6 pounds

Case Quantities Each