

Eos®/Cobalt® Series



GENERAL INFORMATION

The Net3 RVI3 can be used for remote video and local programming functions with Eos and Cobalt family control systems. It provides support for up to three Windows 7-compatible external displays, which may be standard, single or multi-touch. When used with lon®, Element, Congo jr ®. and Congo Kid®, only two displays are supported.

FEATURES

- Local control or synchronization with Eos and Cobalt family control systems
- Access to all programming functions
- 20 user-programmable front panel buttons
- Four front panel LED status indicators
- 2U 19" Rack-mount enclosure
- Supports the iRFR, aRFR, Eos Standard Fader Wings 20/40, Eos and Cobalt programming wings and the Eos and Cobalt Motorized Fader Wings 10/20

INTERFACES

- AC Input (100 240 VAC at 50/60Hz)
- Two individually configurable ethernet ports,
- Three display port connectors for external displays, standard, single-touch or multi-touch
- Five multipurpose USB ports
- Audio In/Out

ORDERING INFORMATION

Net3 Remote Video Interface3 Units

MODEL	DESCRIPTION			
Net3 RVI3	Net3 Remote Video Interface			

Remote Video Interface3 Accessories

MODEL	DESCRIPTION
Eos FW 20	Eos Standard Fader Wing 20
Eos FW 40	Eos Standard Fader Wing 20
Eos PGW	Eos Programming Wing
Eos MFW 10	Eos Motorized Fader Wing 10
Eos MFW 20	Eos Motorized Fader Wing 20
Cobalt PGW	Cobalt Programming Wing
Cobalt MFW10	Cobalt Motorized Fader Wing 10
Cobalt MFW20	Cobalt Motorized Fader Wing 20

See the ETC Net3 product range for I/O gateways.

Ships with

- One three-button scroll mouse and mousepad
- Alpha-numeric keyboard
- Three Active Display Port to DVI adapters



Eos®/Cobalt® Series

PHYSICAL

Net3 Remote Video Interface3 Units Dimensions*

MODEL	HEIGHT		WIDTH		DEPTH	
	inches	mm	inches	mm	inches	mm
Net3 RVI3	3.52	89	17.13	435	13.60	345

Net3 Remote Video Interface3 Units Weights*

MODEL	WEI	GHT	SHIPPING WEIGHT		
	lbs	kgs	lbs	kgs	
Net3 RVI3	22.5	10.21	35	16	

^{*}Weights and dimensions typical







