


XF-3500™ FOG MACHINE



The XF-Series is the new range of professional grade machines from CITC. These powerful fog machines are capable of an output of up to 35,000 CFM, the highest in its class. The XF 3500 & XF-2500 come standard with X-Cradle Impact Armor - a proprietary design, handmade in the USA from aircraft grade materials that protects machines from drops from up to 3 feet. With full featured digital control technology and designed specifically for use with CITCs precision smart fog™, the XF-Series provide the most precise timed applications of fog dispersion anywhere.

FEATURES:

- X-Cradle™ Impact Armor. Drop Tested to Three Feet.
- The Highest Fog Output in its Class at 35,000 cfm.
- Run Dry Fluid Sensor - Protect Your Show & Machine.
- Instant Off & SmartFog™ Technology: The Most Precise Timed Fog System in the Industry.
- Designed & Built in the USA.

1 YEAR WARRANTY

When using CITC SmartFog Fluids.



XF-3500 SPECS

XF-3500 120v #100501

XF-3500 230v #100502

XF-2500 120v #100551

XF-2500 230v #100552

- **Weight:** 35lbs (16kg)
- **Dimensions:** 23.25" x 11.5" x 13.25"
- **Shipping Weight:** 45lbs (20kg)
- **Shipping Box Size:** 25" x 15" x 16" (64 cm x 38 cm x 41 cm)
- **Operation:** DMX, Stand-Alone or Wireless Remote
- **DMX:** Wireless DMX
- **Warm Up Time:** 8 Minutes
- **Heating Unit:** 1500 Watts
- **Electrical Supply:** 120 VAC 15A 60 Hz (230v 8A 50Hz)
- **Breaker:** 120 VAC 15A (230v 7A)
- **CITC SmartFog Precision Fog Fluids:**
 - 15 Second Ultra-Quick
 - 1 Minute Quick Fog
 - 3 Minute (perfect for low-ground fog)
 - 15 Minute
 - 25 Minute Regular
 - 5 Minute Long Lasting
 - 60 Minute Longest Lasting

Specifications	XF-3500	XF-2500	XH-1200	XH-1000
Fog Output	35,000 CFM	25,000 CFM	—	—
Haze Output	—	—	12,000 CFM	10,000 CFM
X-Cradle™ Impact Armor	✓	✓	✓	✓
Clog Resistant System	✓	✓	✓	✓
Core Cleaning < 5min	✓	✓	✓	✓
Designed & Built in the USA	✓	✓	✓	✓
Power On Fog or Haze Ready	8 min	8 min	7 min	7 min
Instant Off Technology	✓	✓	—	—
Fluid Sensor: Auto Run Dry Prevention	✓	—	✓	—
Full RDM Protocol Support	✓	✓	✓	✓
Wireless DMX	✓	Optional	4	Optional
DMX Channels	1	1	2	2
Wireless On/Off Remote Control	Optional	Optional	Optional	Optional
High Capacity Tank	1.5gal 5.7L	1.5gal 5.7L	1.5gal 5.7L	1.5gal 5.7L
Fluid Consumption Rate	50oz/hr	35oz/hr	4oz/hr	4oz/hr
CITC Precision Smart Fog™	✓	✓	—	—
CITC Premium Organic Haze	—	—	✓	✓
CITC Basic Water Haze	—	—	✓	✓
Available in 120v & 230v	✓	✓	✓	✓

X-Cradle Impact Armor: Aircraft rated materials built to cradle the unit from the demands of shipments and daily performances. Drop tested to three feet.

Instant off Technology: Prevents residual fluid in the head from randomly puffing fluids.

Run Dry Fluid Sensor: Protects the pump from burning out when the lines have run dry of fluids.