

ETC Reference Guide

High End Systems HQ-100 Performance Hazer DMX Channel Map

Channel	Description	Value
1	Haze Output OFF	0-4
	Haze Output 1-100%	5-255
2	Blower Volume 1%	0-4
	Blower Volume 2-100%	5-255
3	High Output (HO) Mode OFF	0-126
	High Output (HO) Mode ON	127-255
4	Idle	0-15
	Standard Operation	16-69
	Blower OFF	70-89
	Cool Down	90-109
	Tank Light ON	110-139
	Tank Light OFF	140-159
	Display ON	160-179
	Display OFF	180-199
	All ON (Heater, Blower, Tank Light, Display)	200-219
	All OFF (Heater, Blower, Tank Light, Display)	220-239
	Idle	240-255



Corporate Headquarters ■ Middleton, WI, USA | +1 608 831 4116

Global Offices ■ London, UK | Rome, IT | Holzkirchen, DE | Paris, FR | Hong Kong | Dubai, UAE | Singapore
New York, NY | Orlando, FL | Los Angeles, CA | Austin, TX

Web etconnect.com | **Support** support.etconnect.com | **Contact** etconnect.com/contactETC

© 2021 ETC, Inc. | Trademark and patent info: etconnect.com/ip

Product information and specifications subject to change. ETC intends this document to be provided in its entirety.

1501M2400 Rev A Released 2021-01

ETC Reference Guide

DMX Channel Map

Revision History

Revision A - Initial release. (2021-01)