

SureGrip® Synthetic Rope

- The only theatrical rope with a wear indicator telling you when the rope needs replacing.
- The perfect replacement for manila and other ropes used backstage.
- · Conventional, three-strand construction for a familiar feel and strong grip.
- · Minimal stretch for easy use.
- Length does not change with temperature or humidity, so floor block readjustment is not necessary.
- Breaking strength for 3/4" (19 mm) SureGrip is 10,000 lbs. (4,535 kg), more than twice the strength of manila rope.
- · Tracer tape with manufacturer's name, contact information and year manufactured.
- Sold in 600' (183 m) and 1200' (366 m) rolls.
- US Patent 7,461,500.



SureGrip Synthetic Rope

Order Information

Number	Description	RWL	Weight
028-750SGW6	3/4" (19 mm) Diameter SureGrip	1050 lbs.	0.13 lb./ft.
	600' Roll (183 m)	(476 kg)	(0.19 kg/m)
028-750SGW12	3/4" (19 mm) Diameter SureGrip	1050 lbs.	0.13 lb./ft.
	1200' Roll (366 m)	(476 kg)	(0.19 kg/m)
028-750SGB6	3/4" (19 mm) Diameter SureGrip, Black	1050 lbs.	0.13 lb./ft.
	600' Roll (183 m)	(476 kg)	(0.19 kg/m)
028-750SGB12	3/4" (19 mm) Diameter SureGrip, Black	1050 lbs.	0.13 lb./ft.
	1200' Roll (366 m)	(476 kg)	(0.19 kg/m)
RWL is based on manufacturer's 10:1 safety factor.			











WENGER CORPORATION

Phone 800.4WENGER (493-6437) Worldwide +1.507.455.4100 | Fax 507.455.4258 Worldwide +1.507.774.8576 Parts & Service 800.887.7145 | Canada Office 800.268.0148 | Web wengercorp.com | 555 Park Drive, PO Box 448 | Owatonna | MN 55060-0448

JR CLANCY

Phone 800.836.1885 Worldwide +1.315.451.3440 | Fax 877.836.1885 Worldwide +1.315.451.1766 | Web jrclancy.com 7041 Interstate Island Road | Syracuse | NY 13209-9713