# **SUPERSTAR 600 LED**

## **MODEL 1280**

#### **PROFESSIONAL & VERSATILE**



Beam Angle 7-15°

### **CLASS LEADING OUTPUT**



- f Internal Electronic Flicker Free Power Supply
- \* Variable Focal Optics
- Mechanical Dimming &
  Optional DMX Dimming
- \* Fine Focus Mechanism
- \* Internal Self-Cancelling Color Boomerang
- \* Includes 4 Legged Folding Base with Casters & Leveling Jacks

Lycian advanced technology brings the brightest LED followspots to the entertainment industry. Enjoy the benefits of green technology without sacrificing performance. Brilliance with a clean, well defined beam, the Superstar 600 LED runs cool and quiet. Get the best of all worlds with an LED followspot brighter than the competition while minimizing electrical useage. It's proudly made in America.





### SUPERSTAR 600 MODEL 1280

The luminaire is a 600 watt LED followspot. The spot diameter is controlled by a top- mounted lever which opens and closes a nichrome steel iris. The unit includes a top-operated 3 plate sliding fader and a 6 color self-cancelling color boomerang. A 600 watt LED with heat sink is housed in the rear of the head. Optical quality lenses complete the optical system. The Superstar 600 LED utilizes an electronic switching power supply. The power supply is integrated into the followspot head. A 12 foot Power Con ® power cord with NEMA 5-15 is included. A 4 legged folding base is included. Units are cooled by quiet low volume fans. The housing is constructed of extruded aluminum and cold rolled steel and is powder coated in black and brown. The Lycian Stage Lighting Superstar 600 LED shall be specified. Fixtures are manufactured in USA

SUPERSTAR 600 LED PHOTOMETRICS						
SUPERSTAR OUD LED PHOTOMETRICS						
Distance Feet	65	80	100	115	130	
Distance Meters	19.8	25	30	35	40	
Spot Diameter Ft.	5	8	12	15	20	
Spot Diameter Meters	1.5	2.4	3.7	4.9	6.1	
Flood Diameter Ft.	15'-7"	20'-8"	26'-1"	30'	33'-9"	
Flood Diameter Meters	4.8	6.3	8	9.1	10.3	
Foot Candles Spot	402	266	170	129	101	
Lux Spot	4327	2863	1830	1389	1087	
Foot Candles Flood	113	75	48	21		
Lux Flood	1216	807	517	226		

Beam Angle 7° - 15°

SUPERSTAR 600 LED HEAD DIMENSIONS	ELECTRICAL COMPATABILITY	ORDER INFO
Head Length- 53-3/4"	100-120V, 50/60Hz	Model 1280, Superstar 600 LED
	208-240V, 50/60Hz	Includes Neutrik Power Con®
Base Weight 46 Lbs.	Electric Consumption 4.58A @ 115V	Connector, power cord w/ NEMA
Weight- Head & Yoke- 138 Lbs.	Auto Switching	5-15P, yoke & 4 Legged Base

Specifications subject to change without notice





LYCIAN STAGE LIGHTING

PO Box 214, Sugar Loaf, NY 10981 USA Tel. (845) 469-2285 www.lycian.com