

Lighting Control Console

The introduction of the NEO lighting control console marks a new chapter in the evolution of control. This console allows the ability to seize light; to grab, move, change position, color and motivate the lighting design simply and effectively. The NEO lighting control console is the closest that a designer can get to actually touching the light; encompassing the dreams and aspirations of both professionals and amateurs alike. The NEO lighting control console starts with the inclusion of many timesaving features, allowing the user to program faster and more accurately.



NEO Lighting Control Console

(shown with optional monitor - monitor sold separately)

Icons and Shutter controls are represented graphically on the display,

saving time and presenting meaningful data to the operator. Floating Windows allow the operator to configure their views their way, making it easier to find information. Effects are revolutionized, with "Time Line" features, allowing drag and drop to create that perfectly timed sequence.

The show is even secured on a "Mission Critical" grade SQL server, ensuring no data loss in those critical moments. Boot time is massively reduced with high speed solid state disk drives, making the NEO lighting control console robust for everyday and touring use.

With individually controlled back lit keys, motorized faders, user security system, pixel mapping and media playback: we think you will find the NEO lighting control console a worthy successor to a proud history of iconic consoles that have had the honor of bearing the Strand Lighting and now Philips Strand Lighting name.

Features

- Up to 100 Universes of DMX per Console
- 10 Motorized Submasters
- Motorized A/B Playback Faders
- 5 Motorized Multi-Function Faders
- Dual Motorized Grand Masters
- Individually Controlled Backlit Keys
- 4 Indented Push Encoders
- Color LCD Screens for Encoder Assignment
- Keyboard drawer with storage with USB
- Touchscreen capable interface
- Unlimited Cues, Cue Lists, Groups, Palettes, Effects, and Macros
- Tempo Button
- Tracking, Cue Only and Hybrid Tracking Programming
- Flexible Shortcut System
- Generic Palettes
- Time Line Effects
- Pixel Mapping
- Media Playback
- Multi-User
- Tracking Backup
- User security system (login)
- Timed Events with sunrise/sunset

- Telnet Interface
- Web Server Hosting
- Android / iOS Remotes
- Undo History
- Visual Timecode Editor
- Power Monitor
- Color and Position Paths per Cue
- Blind Pre-Visualization
- Magic Sheet Layout
- 4 DMX Out Ports / 1 DMX In Port / 2 Network Ports
- 3 Video Outs (HDMI / VESA Display Port / DVI)
- MIDI Out / In
- SMPTE Out / In
- USB 3.0 and USB 2.0 Ports
- 2 COM Ports
- 2 XLR Ports for Console Lights
- Tablet Storage


PHILIPS

Strand Lighting

SPECIFICATION SUBMITTAL

CONSULTANT:	PROJECT NAME:	MODEL NUMBER QUANTITY:
DATE:	PROJECT NUMBER:	APPROVED BY:

Strand Lighting



Philips Advantage DMX

Every NEO lighting control console also benefits from the all new Philips Advantage DMX model. This concept allows you to patch Philips Entertainment and Color Kinetics brand luminaires without consuming the console's purchased DMX outputs. It does not matter if you own or rent the luminaires; as long as the one of the supported Philips brands. With Philips Advantage DMX, you can control thousands of Philips luminaires at no additional cost or output license limitations.


Philips Advantage DMX Overview (example):

- A NEO lighting control console is purchased with 1 universe of 512 DMX outputs.
- The purchased universe of 512 DMX outputs is patched to dimmers or other DMX-controlled products.
- Philips Entertainment Group luminaires (sold separately) are patched to any other DMX universe. Philips Entertainment Group luminaires (regardless if you own or rent them) will not count against any of the purchased channels unless patched to the purchased DMX universe.



NEO Lighting Control Console (shown with keyboard drawer open - monitor sold separately)

Product Dimensions



PHILIPS

Strand Lighting

Technical Specifications

Electrical

Supply Voltage: Universal power supply 100-240VAC

Approvals: cETLus, CE, C-Tick

Mechanical

Construction: High Density and Impact Resistant

Aluminum and Plastics

Operating Temperature: 0° to 40° C ambient (32° to 104°F)

Humidity: 0% - 95% non-condensing Storage Temperature: 0° to 35°C (32° to 95°F)

Weight: 37.0 lbs (16.8 kgs) - Console Only (no

accessories)

Protocols / Connectivity

Shownet

E1.31 (Streaming ACN)

ArtnetDMX512

KiNet (Philips Color Kinetics Control Protocol)

PathwayRDM

Connections / Ports

- 4 DMX Out via 5-pin DMX 1 DMX In via 5-pin DMX
- ז אוט זוון אוא טיאט אוו אואט טיאגע זוו אואט ז 1 MIDI In / Out
- 1 SMPTE In / Out
- 1 VESA Display Port
- 1 HDMI Port
- 1 DVI Port
- 2 Network Ports RJ45
- 1 Audio Line In/Out/Mic In via 1/8" mini
- 2 COM ports
- 2 USB 3.0 (on rear panel)
- 7 USB 2.0 (2 on rear panel, 4 on front of console, and 1 in keyboard drawer)
- 2 3-pin XLR ports (12 Volt) for Console Lights (2 console lights are included with each console purchased)







Ordering Information Cat. No. Description

NEO Lighting Control Consoles

91001 NEO Lighting Control Console (One Universe of DMX)

Includes: Console dust cover, universal voltage power supply, IEC Cables (1 each - US, Europe, Asia) Console Lights (2 each), and quick start guide. Monitor not included.

Peripheral Equipment - Cables

95090 DMX512 Control Cable 25' (A5F to A5M) 96456 Ethernet cable 10' 10/100BaseT (RJ-45) 96459 Ethernet cable 25' 10/100BaseT (RJ-45)

Accessories

91001-DC Replacement Dust Cover

91002 One NEO Console Universe of DMX (512 Channels)*

Note: *Up to 100 can be ordered on one console.

91021 21-inch Touch Screen Monitor (Multi-Touch)66219 Additional / Replacement Console Light

Philips Strand Lighting

Dallas

10911 Petal Street Dallas, TX 75238 Tel: +1 (214) 647-7880 Fax: +1 (214) 647-8031 Auckland

19-21 Kawana Street Northcote, Auckland 0627 New Zealand Tel: + 64 9 481 0100 Fax: + 64 9 481 0101

Asia

Unit C, 14/F, Roxy Industrial Centre No. 41-49 Kwai Cheong Road Kwai Chung, N.T., Hong Kong Tel: + 852-2796-9786 Fax: + 852-2798-6545

102615_NA_EUA

Europo

European Service & Distribution Centre Rondweg zuid 85 Winterswijk 7102 JD the Netherlands Tel: +31 (0) 543-542516 www.strandlighting.com

© Philips Group 2014
All rights reserved.
The Company reserves the right
to make any variation in design or
construction to the equipment
described. E&OE

