



KEY FEATURES

- RDM, Art-Net and sACN support
- Factory and user presets for plug and play setups
- POE or USB-C powered
- 99 Internal cues with fade and delay time
- Remote configuration via internal webpage
- Powder-coated compact aluminum housing

SPECIFICATIONS

MOUNTING

- Standalone
- Truss-mount (M10 or M12 mounting hole)
- Wall-mount horizontal or vertical (included)
- DIN Rail horizontal or vertical (included)

CONNECTIONS

Front

- (4) 5pin DMX/RDM optically isolated ports
- Ports are bidirectional for DMX In and Output

Back

- (2) Locking RJ45 Ethernet network connections (1x POE)
- USB-C power option

PHYSICAL

- Length: 133.5 mm (5.3 in.)
- Width: 118 mm (4.6 in.)
- Height: 42 mm (1.65 in.)
- Weight: 0.5 kg (1.1 lbs)

ELECTRICAL

- USB-C 5V
- POE 802.3af

APPROVALS / RATINGS

- CE / FCC / IP20



ORDERING

INCLUDED ITEMS

1.5m Locking power cable (EU or US version)

(2) Wallmount plates

(2) DIN-Rail clamps

SKU

US #: NRE023

EU #: 1330000064

J
R
W

