The Radiance Stadium System. It's a Long Way To The Top...





Complete hazer and fan control is achieved via six DMX channels. Hidden in the base, the fan tray slides smoothly into position, giving the road case full support via the fifth wheel. The Turbo Fan rotates 180 degrees providing wide haze dispersion in forward direction and focused dispersion in reverse direction. This system will push haze up to 2,500 cubic feet per minute.

major advancement in water-based haze technology.

used with the Radiance Stadium System. With an extremely long hang time, it produces a beautiful haze and using it maintains your five-year warranty against manufacturer's

defect.









MODELS	
CLF-2486	Radiance Stadium System 110V
CLF-2488	Radiance Stadium System 220V (CE certified)
CLF-2490	Radiance Stadium System - Road Case Only

RADIANCE HAZER SPECIFICATIONS	
Power Cord:	6 ft - 1.8 m
Heater Watts:	500 Watts
Rating:	110 volt AC 50/60 hz 5 amps.
Regulatory Compliance:	This product has been certified to CSA/UL Standards by QPS Canada Inc.

WARRANTY

The Radiance Stadium System has a five-year warranty against manufacturer's defect provided Ultratec fluids are used.

TURBO FAN SPECIFICATIONS	
Output:	2500 cfm @ 1800 fpm
Power:	3 / 1.5 amps (.3 KW or .4 HP)
Noise Level:	70 dB (full speed focused)
Regulatory Compliance:	This product has been certified to CSA/UL Standards by QPS Canada Inc.


Note: road case is 32" wide x 24" deep x 40" tall and weighs 250 lbs.

Visit www.ultratecfx.com to see available accessories, parts and for a complete set of specifications on all models.

ultratecfx.com

tray provides full support







ships with 5-pin DMX cables installed & daisy chained for quick & easy setup